


GENERAL QUALITY DATA SHEET

Ferrous (II) Sulfate 7-hydrate [ChemPure] ChemElements™

CAS No.	7782-63-0
EC No.	231-753-5
Tariff No.	2833 29 80 00
Material number:	90181030*



Typical properties

Molecular weight:	278,01
Melting point:	>60°C (release of crystalline water)
Solubility in water:	665 g/l (20°C)
Specific gravity:	1,898 g/cm ³
Appearance:	Greenish-blue crystals

Quality: GOST 4148-78 [ChemPure]

1. Assay (FeSO ₄ ·7H ₂ O):	99-101%
2. Water-insoluble matter:	≤0,005%
3. pH 5% solution:	≥3,3
4. Chlorides (Cl):	≤0,0005%
5. Ferric iron (Fe ³⁺):	≤0,03%
6. Phosphates (PO ₄):	≤0,001%
7. Arsenic (As):	≤0,00002%
8. Copper (Cu):	≤0,001%
9. Zinc(Zn):	≤0,005%
10. Manganese (Mn):	≤0,03%
11. Sodium and potassium (Na+K):	≤0,005%
12. Calcium and magnesium (Ca+Mg):	≤0,02%
13. Silicon (Si):	≤0,005%
14. Nickel (Ni):	≤0,007%

PURETECH

[in](#) [f](#) @chemelements

High purity chemicals for various industrial and analytical applications

<http://www.chemelements.life>

GENERAL QUALITY DATA SHEET

Standard packing

- *25 kg three-layer paper brown craft bag with polyethylene inliner (50 µm);
- *25 kg polypropylene bag (60 g/m²) with two inliners: transparent polyethylene liner (50 µm) and black polyethylene liner.

Available on request

*Other customer-specific packing, quality parameters

Shelf life

6 months

Storage recommendation

Store in a cool, dry, ventilated warehouse in the original tightly closed packaging away from sources of heat. Maintain a constant temperature not to exceed 25°C. Avoid exposure to direct sunlight.

Application

- Production of other iron compounds;
- Electrolyte component in electroplating;
- Wood preservative;
- Fungicide;
- Flocculant in wastewater treatment.

Certification

FSSC 22000:2013, ISO 9001:2015, Kosher, Halal MUI

Hazards Identification

Pictogram:



Signal Word:

WARNING

Hazard statements:

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation

Precautionary statements:

P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.



PURETECH

High purity chemicals for various industrial and analytical applications

ChemElements – the alternative producer of high purity mineral salts located in Europe. Raw materials for food, pharmaceutical, feed, agriculture, and technical applications

  @chemelements

<http://www.chemelements.life>



GENERAL QUALITY DATA SHEET

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P330 Rinse mouth.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

Transport Information

UN number:	Not dangerous goods
UN proper shipping name:	Not dangerous goods
Transport hazard class(es)	
Land transport (ADR/RID):	Not classified as dangerous in the meaning of transport regulations
Air transport (IATA):	Not classified as dangerous in the meaning of transport regulations
Sea transport (IMDG):	Not classified as dangerous in the meaning of transport regulations
Packaging group:	Not dangerous goods

Production

CHEMICAL ELEMENTS UKRAINE, LLC
Khimikov avenue, 74, Cherkassy, 18028, Ukraine
+38 0472 59 02 28
hello@chemelements.life
www.chemelements.life

Sales

Chemelements Germany	Chemelements Ukraine	Chemelements Russia
Colonnaden, 5, Hamburg, 20354, Germany +49 40 333 13 237 hello@chemelements.life www.chemelements.life/en	Khimikov avenue, 74, Cherkassy, 18028, Ukraine +38 0472 59 02 28 hello@chemelements.life www.chemelements.life/ua	Kirova street, 26, Staraya Kupavna, 142450, Russia +7 495 662 95 25 hello@chemelements.life www.chemelements.life/ru

Revision Date: May, 2020

This data sheet is for information purposes only and is based on observations of our standard product. It does not release the user from any obligation to test the material and determine suitability for each application.